EVAPCO, INC. evapco UNIT MODEL # DATE SERIAL # REV. NTS CV081208-DRA-HR **EVAPORATIVE CONDENSER** 1. (M)- FAN MOTOR LOCATION **BOTTOM OUTLET** 2. * -APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTION 3. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING 4. + UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE SEPARATE DRAWINGS FOR ACCESSORIES) 7'-10" [2388] 5. 3/4" DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT FACE 2 DRAWING **PLAN VIEW** 6. THE SPRAY PUMP SHOULD BE SIZED FOR 545 GPM AND 2.5 PSIG AT THE INLET CONNECTION 27 [686] (M) 67 1/4 [1708] 18'-2 5/8" [5553] FACE 1 22 * 559] 1 1/2 [38] 13 5/8 * [346] 8 1/4 * [210] 6 FPT 47 * [1194] 75 [1905] INLET (4) 4 [100] BFW REFRIG IN 54 3/4 [1392] 27 * [686] (4) 4 [100] BFW **RÉFRIG OUT** 7'-7" [2311] 79 3/4 0 0 0-[2026] **ACCESS** 5 1/4 * **ACCESS** DOOR 3 1/4 TYP. - [133] 36 1/4 [919] **DOOR** 18'-2 5/8" [5553] 7'-10" 2388 FACE 1 FACE 2 SHIPPING OPERATING NO. OF SHIPPING SECTIONS HEAVIEST SECTION 11300 lbs+ [5126] kg+ 11630 lbs+ [5275] kg+ 11300 lbs+ [5126] kg+ 1 WEIGHT WEIGHT WEIGHT