EVAPCO, INC. UNIT MODEL # DATE SERIAL # **CLOSED CIRCUIT CLOOLER** NTS WZ12123606-ERA-RS eco-ATC-1002A 5/7/2024 NOTES: 1. (M)- FAN MOTOR LOCATION 2. HEAVIEST SECTION IS LOWER SECTION **BOTTOM OUTLET** 3. MPT DENOTES MALE PIPE THREAD (M) FPT DENOTES FEMALE PIPE THREAD 24 1/8 - 71 7/8 BFW DENOTES BEVELED FOR WELDING 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE SEPARATE DRAWINGS FOR ACCESSORIES) 5. 3/4" DIA. MOUNTING HOLES. REFER TO 11'-10" RECOMMENDED STEEL SUPPORT 6. THE SPRAY PUMP SHOULD BE SIZED FOR 1030 GPM AND 4.5 PSIG AT THE INLET CONNECTION FACE 2 7. * - APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING **PLAN VIEW** PIPING 11'-11 3/4" FACE 1 **ACCESS** DOOR - 71 -112 8 FLG. INLET 16' 1" (2) 4 BFW (2) 1/2 FPT **FLÚID OUT VENT** 127 3/4 81 (2) 4 BFW 48 – 19 1/2 FLUID IN 22 7/8 - 11'-10" - 11'-11 3/4" FACE 1 FACE 2 NO. OF SHIPPING SECTIONS **SHIPPING** lbs.+ OPERATING HEAVIEST SECTION 2 15000 18520 lbs. 9295 lbs. WEIGHT WEIGHT WEIGHT