EVAPCO, INC. UNIT MODEL # DATE SERIAL # **CLOSED CIRCUIT CLOOLER** NTS WZ12124806-MRA-RL MTW 8-5L12-Z 5/18/2024 NOTES: 1. (M)- FAN MOTOR LOCATION **BOTTOM OUTLET** 2. HEAVIEST SECTION IS LOWER SECTION 3. MPT DENOTES MALE PIPE THREAD - 1826 613 FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING 4. +UNIT WEIGHT DOES NOT INCLUDE ACCESSORIES (SEE SEPARATE DRAWINGS FOR ACCESSORIES) 5. 19mm DIA. MOUNTING HOLES. REFER TO 3607 RECOMMENDED STEEL SUPPORT 6. THE SPRAY PUMP SHOULD BE SIZED FOR 65 FACE 2 L/S AND 31 kPa AT THE INLET CONNECTION **PLAN VIEW** 7. * - APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING 3651 FACE 1 -178565 **ACCESS** - 1803 – M DOOR 3327 200 FLG. **INLET** 5385 (2) 100 BFW (2) 15 FPT FLUID OUT **VENT** 3550 (2) 100 BFW 2057 1219 495 FLUID IN 581 1194 3607 3651 FACE 2 FACE 1 NO. OF SHIPPING SECTIONS **SHIPPING** OPERATING HEAVIEST SECTION 7115 kq 8710 kg 4215 2 WEIGHT WEIGHT WEIGHT