2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE PE DENOTES PLAIN END	
1. (M)- FAN MOTOR LOCATION 2. HEAVIEST SECTION IS UPPER SECTION 3. MPT DENOTES MALE PIPE THREAD FPT DENOTES FEMALE PIPE THREAD BFW DENOTES BEVELED FOR WELDING GVD DENOTES GROOVED FLG DENOTES FLANGE	
ACCESSORIES (SEE ACCESSORY DRAWINGS) 5. MAKE-UP WATER PRESSURE 20 psi MIN [137 kPa], 50 psi MAX [344 kPa] 6. *-APPROXIMATE DIMENSIONS DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING 7. 3/4" [19mm] DIA. MOUNTING HOLES. REFER TO RECOMMENDED STEEL SUPPORT DRAWING. 8. DIMENSIONS LISTED AS FOLLOWS: ENGLISH FT-IN	FACE D
METRIC [mm] 7" [178] 1'-3 1/4"	
	= -T
3'-3 1/4" * (4) 4' [100] PE REFRIG IN REFRIG OUT (4) 4' [100] PE REFRIG OUT (4) 4' [100] PE REFRIG OUT (5) 4848] (2) 2" [50] MPT (4) 4' [100] PE REFRIG OUT (1884)	
2'-1 1/4" [643] (2) 3" [80] MPT DRAIN [433] (2) 3" [80] MPT OVERFLOW 11'-11 3/4" [108] 7'-2" [2184] 1'-4 3/4" 24'-2"	1'-4 3/4"
11'-10" 24'-2" 7366] FACE B	1'-4 3/4" [425]
SHIPPING 37600 lbs+ [17060] kg+ OPERATING 51560 lbs+ [23390] kg+ HEAVIEST SECTION 16090 lbs+ [7300] kg+ NO. OF SHIPPING SECTIONS	drawn by: SLR