| CONDENSER  |  |   |  | EVAPCO, INC. Evapco                 |                     |         |                        |                              | DWG.# C4122410-DRA-ST - REV - |                |          |
|--|--|---|--|-------------------------------------|---------------------|---------|------------------------|------------------------------|-------------------------------|----------------|----------|
| MODEL#   | ATC-1026E  | SCALE NT  | S                                      | VAPC                                | J, IN               |         |                        | SERIAL#                      |                               | DATE:          | 5/2/2024 |
| 2. MPT DE FPT DEI BFW DE GVD DE FLG DEI PE DEN 3. +UNIT V ACCESS 4. MAKE-L 20 psi M 5. *-APPR FOR PR PIPING 6. 3/4" [19r RECOM | N MOTOR LOCATION NOTES MALE PIPE THOTES FEMALE PIPE NOTES BEVELED FOR NOTES GROOVED NOTES FLANGE OTES PLAIN END VEIGHT DOES NOT INC SORIES (SEE ACCESS P WATER PRESSURE IN [137 kPa], 50 psi MA DXIMATE DIMENSIONS E-FABRICATION OF C  nm] DIA. MOUNTING H MENDED STEEL SUPP IONS LISTED AS FOLI ENGLISH FT-IN | THREAD R WELDING CLUDE GORY DRAWIN E AX [344 kPa] S DO NOT USE ONNECTING HOLES. REFER | E TO                                   |                                     | FACE B<br>PLAN VIEW |         | ACCESS I               | FACE C                       |                               | DESS DOOR      | FACE D   |
|  | METRIC [mm]  |   |  |                                     |                     |         |                        | FACE A                       |                               |                |          |
|  |  | _   | Ī                                      | -7" [178]                           | 1'-3 1/4" [3        | 8871—   | _                      |                              | _                             |                |          |
|  |  |   |  |                                     | ) +11 0-1           | ,07]    |                        |                              |                               |                |          |
|  |  | 5'-9 3/8"*<br>[1762]  | 4'-8 1/8"[14:<br>3'-0 3/8" *<br>[922]  | 26]                                 |                     |         | (M) ACCE               |                              |                               | ACCESS<br>DOOR |          |
| 4'-0 3/4"[12   | (2) 4* [100] PE  | REFRIG O  | 6'-0"[18                               | 29]<br>'-10 1/2" [5143]             |                     |         | 6/>                    |                              |                               |                |          |
| 2" [50] MPT<br>MAKE-UP<br>3" [80] MPT<br>DRAIN<br>   |  |   | 6" [152] *<br>6'-2 3/8" [18            | 889]                                |                     |         |                        |                              |                               |                |          |
| 3 5/8" [92] 5 1/4"<br>[133]<br>4 1/4"<br>[108]<br>7'-2"<br>[2184]<br>11'-10"   |  |   | -1'-5" [432]<br>-3" [80] MP<br>OVERFLO | 2'-10 3/8" 24'-<br>801 MPT [873] [7 |                     |         |                        | 24'-1 3/ <u>4'</u><br>[7360] |                               |                |          |
|  | ı  | [3607]<br>ACE B   | <del></del>                            |                                     |                     |         |                        | FACE A                       | 7                             |                |          |
| SHIPPING<br>WEIGHT   | 38540 lbs+ [17485]   | kg+   | OPERATING 5158                         | 0 lbs+ [23400] kg+                  | HEAVIEST<br>WEIG    | SECTION | 31920 lbs+ [14480] kg+ | NO. OF SHIPPIN               | NG SECTIONS 2                 | DRAWN BY:      | JLG      |